

Model(s)	EWYE035CZN-A1		
Air-to-water heat pump	YES		
Water-to-water heat pump	NO		
Brine-to-water heat pump	NO		
Low-temperature heat pump	NO		
Equipped with a supplementary heater	NO		
Heat pump combination heater	NO		
Parameters shall be declared for medium-temperature application, except for low-temperature heat pumps. For low-temperature heat pumps, parameters shall be declared for low-temperature application. Parameters shall be declared for average, colder and warmer climate conditions.			
Item	Symbol	Value	Unit
Rated heat output ⁽³⁾	Prated	23,8	kW
<i>Declared capacity for heating for part load at indoor temperature 20°C and outdoor</i>			
T _j = - 7°C	P _{dh}	21,0	kW
T _j = + 2°C	P _{dh}	13,2	kW
T _j = + 7°C	P _{dh}	8,3	kW
T _j = + 12°C	P _{dh}	3,6	kW
T _j = bivalent temperature	P _{dh}	21,0	kW
T _j = operation limit temperature	P _{dh}	19,8	kW
For air-to-air heat pumps: T _j = - 15 °C (if TOL < - 20 °C)	P _{dh}	-	kW
Bivalent temperature	T _{biv}	-7	°C
Cycling interval capacity for heating	P _{cyc}	-	kW
Degradation co-efficient (4)	C _{dh}	0,94	-
Power consumption in modes other than active mode			
Off mode	P _{OFF}	0,000	kW
Thermostat-off mode	P _{TO}	0,146	kW
Standby mode	P _{SB}	0,070	kW
Crankcase heater mode	P _{CK}	0,070	kW
Other items			
Capacity control	Variable		
Sound power level, indoor/outdoor	L _{WA}	77	dB
Annual energy consumption	Q _{HE}	14459,9	kWh
For heat pump combination heater:			
Declared load profile	-		
Daily electricity consumption	Q _{elec}	-	kWh
Annual electricity consumption	AEC	-	kWh
Daikin Applied Europe - Via Piani di S.Maria 72, 00040 Ariccia (Roma), Italy			
Item	Symbol	Value	Unit
Seasonal space heating energy efficiency	η_s	125%	%
<i>Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20°C and outdoor temperature T_j</i>			
T _j = - 7°C	COP _d or PER _d	1,91	%
T _j = + 2°C	COP _d or PER _d	2,87	%
T _j = + 7°C	COP _d or PER _d	4,96	%
T _j = + 12°C	COP _d or PER _d	6,70	%
T _j = bivalent temperature	COP _d or PER _d	1,91	%
T _j = operation limit temperature	COP _d or PER _d	1,74	%
For air-to-air heat pumps: T _j = - 15 °C (if TOL < - 20 °C)	COP _d or PER _d	-	%
For air-to-water heat pumps: Operation limit temperature	COP _d or PER _d	-25	°C
Cycling interval efficiency	COP _{cyc} or PER _{cyc}	-	%
Heating water operating limit temperature	WTOL	70	°C
Equipped with a supplementary heater:			
Rated heat output (4)	P _{sup}	2,6	kW
Type of energy input	Electric		
Other items			
For air-to-water heat pumps: Rated air flow rate, outdoors	-	22068	m ³ /h
For water- or brine-to-water heat pumps: Rated brine or water flow rate, outdoor heat exchanger	-	-	m ³ /h
For heat pump combination heater:			
Water heating energy efficiency	η _{wh}	-	%
Daily fuel consumption	Q _{fuel}	-	kWh
Annual fuel consumption	AFC	-	GJ
Daikin Applied Europe			
(3) For heat pump space heaters and heat pump combination heaters, the rated heat output 'Prated' is equal to the design load for heating 'Pdesignh', and the rated heat output of a supplementary heater 'Psup' is equal to the supplementary capacity for heating 'sup(Tj)'. (4) If 'Cdh' is not determined by measurement then the default degradation coefficient is 'Cdh'= 0,9.			