

Information requirements for comfort chillers								
EWFD430TZSSD1								
Outdoor side heat exchanger of air conditioner: Air								
Indoor side heat exchanger of air conditioner: water								
Type: Inverter								
Driver of compressor: Electric								
Item	Symbol	Value	Unit		Item	Symbol	Value	Unit
Rated cooling capacity	Prated,c	424.55	kW		Seasonal space cooling energy efficiency	$\eta_{s,c}$	226.08	%
Declared cooling capacity for part load at given outdoor temperatures Tj and indoor 27°/19 °C (dry/wet bulb)				Declared energy efficiency ratio or gas utilisation efficiency/auxiliary energy factor for part load at given outdoor temperatures Tj				
Tj = + 35 °C	Pdc	424.55	kW		Tj = + 35 °C	EERd or GUEc,bin /AEFc,bin	3.167	
Tj = + 30 °C	Pdc	304.97	kW		Tj = + 30 °C	EERd or GUEc,bin /AEFc,bin	4.497	
Tj = + 25 °C	Pdc	193.67	kW		Tj = + 25 °C	EERd or GUEc,bin /AEFc,bin	6.189	
Tj = + 20 °C	Pdc	89.16	kW		Tj = + 20 °C	EERd or GUEc,bin /AEFc,bin	8.567	
Degradation coefficient for air conditioners (*9)	Cdc	0.9	—					
Power consumption in modes other than 'active mode'								
Off mode	POFF	0	kW		Crankcase heater mode	PCK	0	kW
Thermostat-off mode	PTO	0.13	kW		Standby mode	PSB	0.05	kW
Other items								
Capacity control	Variable				For air-to-water comfort chillers: air flow rate, outdoor measured	—	162036	m3/h
Sound power level, outdoor	LWA	97.7	dB		For water/brine-to-water chillers:	—		m3/h
Emissions of nitrogen oxides (if applicable)	NOx (*10)		mg/kWh input GCV		Rated brine or water flow rate, outdoor side heat exchanger			
GWP of the refrigerant		1430	kg CO2eq (100 years)					
Standard rating conditions used: Low Temp Application								
Contact details	Daikin Applied Europe S.p.A. Via Piani di Santa Maria, 72 00072 Ariccia Roma							